

Smart NH4





Payload up to
200 Kg ■

Maximum horizontal reach
3.150 mm ■

Repeatability
0,1 mm ■



Hollow Wrist




SHELF VERSION

- Handling
- Packaging
- Spot Welding

ROBOT APPLICATIONS

Model	NH4 200-2.7	NH4 165-3.0	NH4 200-3.1/SH - Shelf	
Number of axes	6	6	6	
Load at wrist (Kg)	200	165	200	
Additional load on forearm (Kg)	50	50	50	
Torque of axes (Nm)				
	4	981	981	
	5	981	981	
	6	687	687	
Axes stroke (Speed)				
	1	+/- 180° (85°/s)	+/- 180° (85°/s)	+/- 180° (85°/s)
	2	+75°-60° (90°/s)	+75°-60° (90°/s)	+160°-30° (78°/s)
	3	+110°-170° (90°/s)	+110°-170° (90°/s)	+110°-170° (90°/s)
	4	+/- 200° (143°/s)	+/- 200° (143°/s)	+/- 200° (143°/s)
	5	+/- 200° (143°/s)	+/- 200° (143°/s)	+/- 200° (143°/s)
	6	+/- 200° (205°/s)	+/- 200° (205°/s)	+/- 200° (205°/s)
Repeatability ISO 9283 (mm)	0,1	0,15	0,15	
Maximum horizontal reach (mm)	2.700	3.000	3.150	
Installation position	Floor	Floor	Floor/Shelf	
Protection Class	IP65	IP65	IP65	
Operating Areas (mm)				
	A	3.250	3.543	3.200
	B	2.707	3.000	3.150
	C	1.857	1.857	1.932
	D	1.503	1.796	925
	E	123	169	1.425
Foundry version	Not Available	Not Available	Not Available	

Sales • +39 011 0045406 • sales.robotics@comau.com
 Service • +39 011 0045553 • service.robotics@comau.com
www.comau.com/robotics



The information contained in this brochure is supplied for information only. Comau S.p.A. reserves the right to alter specifications at any time without notice for technical or commercial reasons. The illustration does not necessarily show the products in their standard version. Design by amodo.it - ref.tas.hx06 - Printed in Italy by Graj Art - 05/06 - Turin